




fiorentini

w e c l e a n t h e w o r l d

S28



caratteristiche tecniche	technical specification	caractéristiques techniques		S 28 B	S 28 S	S 28 D
larghezza utile lavoro	scrubbing width	largeur de nettoyage	mm	900	900	900
larghezza utile lavoro (2sp)	scrubbing width (2br)	largeur de nettoyage (2br)	mm	1100	1100	1100
rendimento orario max	cleaning capacity up to	rendement jusqu'à	mq/h	5000	6600	6600
autonomia	operating range	autonomie	h	4	/	/
capacità contenitore rifiuti	waste tank capacity	capacité bac de vidange	L	70	70	70
superficie filtrante	filtering surface	surface filtrante	m ²	6	6	6
velocità di avanzamento	forward speed	vitesse d'avancement	km/h	0-5	0-6	0-6
max pendenza	max. slope	pente max. surmontable	%	10	10	10
rumorosità	noise level	bruit	dB	68	75	75
raggio sterzata	turning radius	rayon de virage	mm	1520	1520	1520
alimentazione	voltage	alimentation		S 28 B	S 28 S	S 28 D
motore aspirazione	vacuum motor	moteur d'aspiration		24v/ 180v		
motore spazzola centrale	central brush motor	moteur de la brosse centrale		24v / 650v		
motore spazzola laterale	side brush motor	moteur de la brosse latérale		24v/ 100v		
motore trazione	traction motor	moteur traction		24v / 700v		
alimentazione	feeding	alimentation		batterie 24 V 4x6V - 330 A	benzina	diesel
potenza cilindri	power cylinders	puissance cylindres		/	6 cv/ 1 CL	37 cv/ 1 CL
raffreddamento	cooling	refroidissement		/	aria/ air / aèrien	aria/ air / aèrien
dimensioni	dimensions	dimensions		S 28 B	S 28 S	S 28 D
dimensioni	dimensions	dimensions	mm	1390x875x 1178	1390x875x 1178	1390x875x 1178
spazzola centrale	central brush	brosse centrale	mm	Ø 265 x 700mm	Ø 265 x 700 mm	Ø 265 x 700 mm
spazzola laterale	lateral brush	brosse laterale	mm	Ø 400	Ø 400	Ø 400
peso macchina	weight of the machine	poids de la machine	kg	270	336	336
opzionale	optional	optionnelle		S 28 B	S 28 S	S 28 D
scarico alto	hydraulic high dump	déchargement hydraulique		elettrico e idraulico/electric hydraulic/électrique et hydraulique		
altezza scarico	dumping height	hauteur de décharge	mm	1310		
dimensioni	dimensions	dimensions	mm	1470x 915x1440		



stabilimenti produttivi

50033 Piancaldoli (FI) via Piancaldoli 1896 Firenzeuola
tel +39 0558173610 - fax +39 055817144

50033 Pietramala (FI) via pietramala 70/B
tel +39 055813447 - fax +39 055813504

40024 Castel San Pietro (BO) via Cà Bianca 231/C
tel +39 051941743 - fax +39 0516942400

filiali commerciali

20132 Milano via Palmanova 211/A
tel +39 0227207783 - fax +39 022592779

00012 Guidonia Montecelio (Roma) via Bruno Pontecorvo 20
tel +39 0774357184 - fax +39 0774353419

dati aziendali

ing. O. Fiorentini s.p.a. via Piancaldoli, 1896 - Firenzeuola

50033 Fraz. Piancaldoli (FI) - Italia

P.I. 06113160482

Certificazione ISO 9001:2015

e-Mail: info@ingfiorentini.it